



EXAMPLE: Settlement / Vertical Offset

(1) Curb and/or gutter having differential settlement or heaving at joints that create a vertical offset of 2 inches or more at any point along a joint,...or multiple joint gaps greater than 3 inches



EXAMPLE: Extreme Slope

(2) Curb and/or gutter having a slope of more than 2 inches per foot in any direction from a road or natural grade that creates a discontinuation in the curb or gutter.



EXAMPLE: Large Holes in Surface

(3) Curb and/or gutter having holes or depressions in the surface that are in excess of 1 foot by 1 foot by 2 inches deep.



EXAMPLE: Deteriorated

(4) The surface of a curb and/or gutter having 50% or greater of its surface continuously spalled or deteriorated within a 10 ft poured section.



EXAMPLE: Exposed aggregate

(5) Curb and/or gutter sections that have crushed stone or gouges that continuously expose aggregate for 50% or more within a 10 ft poured section.



EXAMPLE: Asphalt repairs

(6) Curb and/or gutter sections that have been previously patched with a bituminous material or materials other than concrete for 50% or more within a 10 ft poured section. (This does not include a street or section of a street originally installed or reconstructed with asphalt curbing and/or gutter.)



CITY OF
SIDNEY

REPLACEMENT CRITERIA FOR CURB AND GUTTER

REVISIONS: DATE APPROVED
06/03/2020
PAGE No.
300-22