



\* MIN. 18" WIDTH IF ASPHALT BACKFILL IS USED IN THE REPAIR.

\*\* CONCRETE OR 301 ASPHALT AGGREGATE BASE TO MATCH EXISTING CONDITION.

#### TYPICAL PAVEMENT RESTORATION DETAIL

#### TYPICAL PAVEMENT RESTORATION NOTES

##### MINIMUM GRAVEL PAVEMENT REPLACEMENT

2" OF ODOT #67 ON

12" OF ODOT ITEM 304, IN LIFTS OF 3" MAXIMUM

##### MINIMUM ASPHALT PAVEMENT REPLACEMENT

PERMANENT PAVEMENT REPLACEMENT SHALL MATCH EXISTING PAVEMENT THICKNESS, BUT MUST BE A MINIMUM OF 3-1/2 INCHES, WHICHEVER IS GREATER. (MINIMUM PAVEMENT COMPOSITION SEE PAGE 300-2 UTILIZING APPROPRIATE STREET CLASSIFICATION).

SOIL BORINGS SHALL BE CAPPED WITH A MINIMUM OF 9" OF ODOT CLASS C CONCRETE.

\* SEE CITY CODE SECTION 907.21 FOR ADDITIONAL REQUIREMENTS



CITY OF  
SIDNEY

## TYPICAL PAVEMENT RESTORATION DETAIL

REVISIONS: 10-12-09	DATE APPROVED: 06/03/2020
PAGE No. 300-21	